



Harrier 25 MK II (2017)

Standard Equipment List

Specifications

LOA	25' 0"
Beam	9' 0"
Draft (hull/prop)	1' 6"/3' 0"
Displacement	7,000 lbs. (fully loaded)
Fuel Capacity	85 U.S. Gallons (Gas) / 100 U.S. Gallons (Diesel & Outboard)
Water Capacity	15 U.S. Gallons
Top Speed (std pwr)	33 kts.

Hull

Solid E-glass bottom laminate
 Foam-cored topsides
 Vinylester osmosis barrier
 Foam-cored E-glass stringers & bulkheads
 Painted bilge
 Custom louvered vents painted to match hull
 Extruded vinyl sheer guard
 Molded interior liner
 Oyster white gel coat hull
 Single boot stripe in choice of color

Deck

Deck	E-glass fabric with foam-cored laminate & molded non-skid pattern Oyster white gel coat finish
Swim platform	Teak with S.S. swim ladder & S.S. handle on transom
Anchor locker	Molded into foredeck with hinged hatch
Handrails	(2) S.S. foredeck handrails (1) on each side of Lewmar foredeck hatch
Chocks	(2) S.S. bow chocks
Cleats	(4) pull-up S.S. 8" cleats & (1) 10" bow cleat
Ensign	Custom teak staff (varnished) with US flag & S.S. socket
Burgee	Teak burgee staff on bow with Hunt Burgee
Windshield	White powder-coated with handrails, side vents & Solex glass
Wipers	Pantograph port & starboard with windshield washers
Lights	LED USCG-approved running lights
Hatch	Lewmar cabin hatch with screen
Fender pad eyes	(4) Wichard pad eyes (2) port & (2) starboard
Fills	S.S. water, fuel & waste
Rod holders	(2) S.S.
Stern eyes	(2) S.S.
Drink holders	(5) one at helm, two portside & two on engine box
Transom locker	(2) molded into transom / drains
Foam	High density foam core in way of high load hardware

Specifications and pricing are subject to change without notice.

June 9, 2016

Cabin

Access	Varnished teak companionway doors and sliding hatch (with covers)
Berths	V-berth with storage under in choice of Sunbrella fabric
Head	Electric saltwater head with Y-valve & holding tank
Lighting	S.S. dome light
Storage	Locker to port
Cabin sole	Faux teak & holly sole
Interior	Fiberglass overhead deck liner

Cockpit

Bimini top	S.S. Bimini bow with S. S. handholds port / stbd sides with Stamoid Bimini top & clear vinyl front filler curtain
Covers	Stamoid covers for teak companion way, helm console, electrical panel, p/s glove box and wet bar
Curtain package	Includes side (with zip-out openings), front and stern curtains (3-pieces) with clear vinyl
Helm	Fiberglass control console with varnished teak shelf, handholds & trim; custom wood. steering wheel
Compass	Ritchie (calibration included)
Seating	Adjustable sport helm seat with storage beneath; adjustable sport companionway seat with insulated cooler beneath; engine-box seat cushion with seat back; Molded L-settee with cushions (includes engine box seat back).
Cushions	Majilite with perforated center panels and choice of contrasting piping
Wet bar	Corian counter top with Corian cover, S.S. cold-water pressure sink, varnished teak fiddles, 12-volt S.S. refrigerator, & tip-out waste bin
Drainage	Self-bailing cockpit with guttered hatches
Shower	Cold pressure water on transom
Lighting	(2) LED courtesy bridgedeck lights, LED strip lighting under coaming in cockpit and lighting in forward sole compartment
Straps	(3) Safety straps on bimini top on both port and starboard side

Mechanical & Electrical

Engine	Volvo Penta EVC 5.3L (300 hp) gas with jackshaft / OceanX stern drive, fresh water cooled; Volvo Penta 2+3 year gas engine warranty Automatic fire extinguisher system in engine compartment (gas engine only) Engine data to interface with chartplotter
Propellers	(2) counter-rotating, S.S. 3-bladed props
Steering	Hydraulic
Sound reduction	Composite sound-reduction insulation 2"
Cooling	Raw-water, sea strainer, seacock with thru-hull intake
Fuel	(2) 42-gallon tanks (gas); (2) 50-gallon tanks (diesel); (1) 100-gallon tank (gas)
Water	(1) 15-gallon tank
Bilge pumps	(1) 1,100 GPH aft (automatic), (1) 2000 GPH midships (automatic), high-water bilge alarm
Batteries	(2) 12-volt marine-grade AGM, 10-amp battery charger, transom-mounted rotary switch
VHF radio	ICOM M324 DSC
Electrical outlet	(1) 12-volt outlet at helm
Horn	AFI flush-mount 12-volt air horn

Commissioning Package

Bottom paint	(2) coats ablative paint; hand-painted outdrive
Name & hailport	Vinyl letters in any color & style
Anchor	14 lb. Delta with 15' x ¼" chain, 200' x ½" rode
Boat gear	(4) 25' x ½" braided docklines; (3) fenders 6" x 15", (2) fender hooks to (2) Fenders, Polartech covers & 3/8" braided line; (1) 36-qt. cooler; (1) boat hook; (1) qt. synthetic gear oil; (1) qt. power-steering / trim fluid; (1) qt. Neutra-salt solution
Safety gear	(4) Type II PFD lifejackets in bag; (1) fire extinguisher; (1) hand-held canister airhorn; (1) throwable floating device (square cushion); (2) plastic whistles; (4) hand-held flares; flashlight with batteries; basic first-aid kit.
Burgee	Teak burgee staff on bow with Hunt Burgee
Documentation	U.S. Coast Guard documents