



Surfhunter 32 (2016)

Standard Equipment List

Specifications

LOA	32' 1"
Beam	10' 6"
Draft (hull/prop)	1' 6"/3' 0"
Displacement	9,000 lbs. (fully loaded)
Fuel Capacity	235 U.S. Gallons
Water Capacity	28 U.S. Gallons
Top Speed (std pwr)	44 kts.

Hull

Solid E-glass bottom laminate
 Foam-cored topsides
 Vinylester osmosis barrier
 Foam-cored E-glass stringers & bulkheads
 Painted bilge
 Extruded vinyl sheer guard
 Molded interior liner
 White gel coat hull
 Single boot stripe in choice of color
 Vinyl goldleaf cove stripe

Deck

Deck	E-glass fabric with foam-cored laminate & molded non-skid pattern Oyster white gel coat finish
Swim platform	Armstrong outboard bracket with telescoping swim ladder and composite teak
Anchor locker	Molded into foredeck with hinged hatch
Bowrail	Custom S.S. bowrail
Chocks	(2) S.S. bow chocks
Cleats	(4) pull-up S.S. 8" cleats & (1) 10" bow cleat
Ensign	Custom teak staff (varnished) with US flag & S.S. socket
Burgee	Teak burgee staff on bow with Hunt Burgee
Windshield	White powder-coated with handrails, side vents & Solex glass
Wipers	Pantograph port & starboard with windshield washers
Lights	LED USCG-approved running lights
Hatch	Lewmar cabin hatch with screen
Portlights	(4) Lewmar, opening with screens
Fender pad eyes	(4) Wichard pad eyes (2) port & (2) starboard
Fills	S.S. water, fuel & waste
Rod holders	(2) S.S. flush-mount holders; (6) under-gunwale rod racks
Drink holders	(5) one at helm, two portside (in varnished teak frame), two on aft amenity
Transom locker	(1) molded into transom
Trunk cabin	Custom vinyl decal stripe
Foam	High density foam core in way of high load hardware

Interior

Access	Varnished teak companionway doors and folding hatch (with Stamoid cover) – storage in companion step
Berths	V-berth with storage underneath & choice of Sunbrella fabric
Head	Enclosed head with shower, shower curtain & sump pump; hot & cold pressure water, S.S. sink with Corian countertop and satin-finish cherry storage cabinets; electric freshwater toilet with Y-valve & 15-gallon holding tank; towel rack and clothes hooks & active solar vent
Cabin sole	Faux teak and holly
Galley	Single-burner portable butane stove; hot & cold pressure water, S.S. sink, refrigerator (110 volt / 12 volt); Corian countertop and satin-finish cherry storage cabinets; and microwave
Wood trim	Satin-finish cherry bulkhead trim and fiddles

Cockpit

Convertible top	S.S. Bimini bow with Stamoid top
Covers	Stamoid covers for teak companion way, helm console, electrical panel, port side drink holder
Curtain package	Includes side (with zip-out openings), front and stern curtains (3-pieces) with clear vinyl
Helm	Fiberglass control console with varnished teak shelf, handholds & trim; custom varnished teak wheel; custom teak engine-instrument cluster and S.S. drink holder with Stamoid cover
Compass	Ritchie (calibration included)
Seating	L-settee with storage & custom bolster back rest; teak ladder-back pedestal helm seat with teak arms and adjustable pedestal base; L – shaped aft seating
Cushions	Hand-stitched, Majilite with choice of contrasting piping
Table	Custom teak bridgedeck table (varnished) with removable S.S. pedestal base, padded Stamoid cover & storage bag for table pedestal
Amenity	Top loading icebox or storage compartment with drawers below. Corian top, S.S. handrail mounted on varnished teak trim
Storage	Starboard-side locker; seat-box compartment and under L-settee
Drainage	Self-bailing cockpit, with guttered hatches
Shower	Hot & cold pressure shower on transom
Lighting	(2) LED courtesy bridgedeck lights, LED strip lighting under cockpit coaming in cockpit and lighting in forward sole compartment

Mechanical & Electrical

Engines	Twin Yamaha F250 four stroke outboards
Propellers	S.S. 3-bladed props
Steering	Power-assisted hydraulic with tilt wheel
Bow thruster	Electric, with joystick control
Trim Tabs	Lectrotab with automatic leveling control
Fuel	(1) 235-gallon tank (gas)
Water	(1) 28-gallon tank; hot and cold pressure water system; 6-gallon water heater
Bilge pumps	(1) 1,100 GPH aft (automatic) & (1) 2000 GPH midships (automatic), high water bilge alarm
Batteries	(2) 12-volt marine AGM batteries; circuit-breaker panel with battery switch
VHF radio	ICOM M324 DSC VHF
Electrical outlet	(1) 30-amp shore power; (3) 110-volt shore-power outlets; (1) 12-volt outlet at helm
Horn	AFI flush-mount 12-volt air horn
Inverter / Charger	(1800 watt) with upgraded battery capacity; 40-amp battery charger
Galvanic isolator	For shore-power system

Commissioning Package

Bottom paint	(2) coats ablative paint
Name & hailport	Vinyl letters in any color & style
Anchor	14 lb. Delta with 15' x 1/4" chain, 200' x 1/2" rode
Boat gear	(4) 35' x 1/2" braided docklines; (3) fenders 8" x 20", (2) fender hooks to (2) fenders, Polartech covers & 3/8" braided line; (1) 36-qt. cooler; (1) boat hook; (1) qt. synthetic gear oil; (1) qt. power-steering / trim fluid; (1) qt. Neutra-salt fluid; spare fuse kit
Safety gear	(4) Type II PFD lifejackets in bag; (1) fire extinguisher; (1) hand-held canister airhorn; (1) throwable floating device (square cushion); (2) plastic whistles; (4) flares; flashlight with batteries; basic first-aid kit
Documentation	U.S. Coast Guard documents