



Hunt 46 Ocean Series Standard Equipment List

SPECIFICATIONS

Length Overall:	45'-10" (14m) *excluding swim platform
Length, on datum waterline:	41'-5" (12.62m)
Molded Beam:	14'-6" (4.42m)
Draft, hull (vs. datum WL):	2'-9" (0.84 m)
Draft, props (vs. datum WL):	4'-0" (1.22m)
Air draft (vs. datum WL):	15'-4" (4.67m)
Deadrise at transom:	20°
Displacement (half load):	35,000 lbs.(15.6 LT)
Fuel capacity:	450 USG (1,700 L)
Fresh water capacity:	120 USG (450 L)
Black water capacity:	40 USG (150 L)

PERFORMANCE

Power:	Volvo Penta IPS600, 435 HP
Speed, maximum (half load):	Std. Power 27 kts Opt. Power 31 kts
Fast cruise (half load):	Std. Power 24 kts Opt. Power 27 kts
Range:	275 nm (10% reserve)
Optional:	IPS 800, 625 HP
Generator:	Northern Lights 12 KW with sound shield

INTERIOR OUTFIT -COMMON INTERIOR FEATURES

Blinds:	Roman-Style in salon. Rolled covers in cabin.
Décor package:	Owners choice of Hunt approved fabrics for salon and cockpit seats.
Doors, cabin:	Painted shaker style framed panels
Doors, locker:	Off white painted plantation shutter style louvered doors
Drawers:	Off white painted shaker-style framed drawer fronts
Grab rails:	Custom Stainless/ teak
Hanging lockers:	Cedar lined in master stateroom,
Hardware:	Seasmart stainless steel blind catches for drawers and cabinets, Mobella McCoy SouthCo Single lever for doors.
Headlining's:	Painted bead board with painted battens
Insect screen/blinds:	Ocean air blinds and screens on overhead hatches
Lighting:	All lights to LED
Outlets and switches:	Vimar switches and outlets
Soles, deckhouse:	Teak & holly
Soles, heads:	FRP and solid teak grating
Soles, staterooms:	Teak & holly
Stairs:	Teak and holly tread with stainless steel support
Interior finish:	Off white paint and satin varnish
Wall coverings:	Off-white painted wood
Wood, interior:	Off white painted surfaces and quarter sawn solid teak accents

SALON

Chart desk:	Opposite to helm.
Helm console:	Volvo controls, instruments and alarms, Ritchie compass, and windlass controls. Provision for navigation electronics equipment, 12 V DC outlets
Steering wheel:	Teak and stainless steel
Seat, companion:	Custom banquette with footrest; stowage beneath.
Seat, helm:	Custom banquette and footrest
Settee:	Built-in, with stowage beneath
Table:	Varnished teak top with companion ottoman.
TV:	28" Samsung H4000 TV on a motorized lift with Apple TV
Hatches:	(2) Manship 16x16 Stainless Steel. Fitted with screens and blinds.

GALLEY/DINETTE

Cook top:	White, double burner, 230 VA, Kenyon
Countertop:	Solid Surface, Drawers: For cutlery and stowage
Exhaust fan:	Above cook top, 24VDC
Lockers:	Beneath countertop, outboard of countertop
Microwave:	Stainless steel, 115V AC
Refrigerator:	U-Line (2) drawer
Outlets:	GFI protected
Dinette:	Leather and teak bench seats with fixed teak table
Sink fixtures:	Wall mounted faucet and handles.
Sink:	Blanco single bowl; under mounted.
Trash container:	Slide out plastic bin.
Freezer:	Isotherm top loading

MASTER STATEROOM

Berth:	Tapered queen-size with drawers and top-access stowage beneath. Premium mattress with inner springs
Bureaus:	(2) with drawers and lockers; port and starboard at hull sides.
Hanging lockers:	(2) cedar lined; micro switches for LED closet lights.
Hatches:	(1) in stateroom.
Mirror:	Full length on stateroom door.
Portlights:	(2) fixed in stateroom.
Hatch:	(1) Manship® LDH-50-I 19-1/2" x 19-1/2"; Hatch fitted with Manship screens/blinds.
TV:	24" Samsung H4500 TV on a swing mount with Apple TV

MID CABIN

Hanging locker:	Cedar lined; micro switch for LED closet light.
Portlights:	(1) Fixed portlight
Bureau:	(1) with drawers
Berths:	Twin converts to Double Mattress - premium grade foam

MASTER HEAD

Exhaust Blower:	24V DC.
Head Accessories:	Towel racks, rings, hooks, soap trays, toothbrush holder, vanity mirror, toilet paper holder.
Head Stowage:	Linen locker with shelves outboard of shower; drawers and locker beneath vanity; lockers above vanity.
Head Configuration:	Split style with separate shower and shower access.
Mirrors:	(1) full length on head door, (1) at vanity.
Portlights:	(1) in shower.
Hatch:	(1) Manship® LDH-08-I 8-1/8" x 13-3/4". Hatch fitted with Manship screens/blinds.
Shower Fixtures:	Single-lever anti-scald type with rail-mounted hand-held shower head.
Shower Stall:	Moulded Oyster White FRP enclosure with seat
Shower Sump:	24V DC.
Sink Fixtures:	Single Grohe in-wall fixture.
Sink:	White sink.
Toilet:	Jabsco Quiet Flush
Vanity Top:	Solid surface
Outlet:	GFI protected

CONSTRUCTION

Hull Lamination:	Vinylester-infused foam-cored laminate above and below water line.
Hull Structure:	Lightweight composite FRP stringers and frames.
Engine-Bed Structure:	Stringer design with high-density foam.
Deck Lamination:	Vacuum-bagged PVC foam core for vertical and horizontal areas.
Deck and Husetop Structure:	Composite FRP beams and frames.
Deck-Hardware Installation:	High-density core in way of hardware.
Deck-Hull joint:	Fully bonded and mechanically fastened.
Bulkheads, Structural:	Vacuum-bagged cored composite.
Bulkheads:	Fully laminated bulkheads.
Cabin Soles, Structural:	Vacuum-bagged cored composite, with sound-proof features.
Gelcoat:	White for deck.
Hull Identification:	Mark & logo
Hull Color:	White

MECHANICAL AND PLUMBING

Air Conditioning:	MarineAir self-contained (4) zones. (2) 16KBTU, (1) 12KBTU, (1)10KBTU.
Automatic Bilge Pumps:	(3) Rule® submersible in (3) zones; 24V DC. Pumps fitted with high-water switches and alarms.
Discharge Pump:	For black water tank, 24V DC.
Engine Mounts:	Volvo isolation mounts.
Engine Room Access:	Via ladder and hatch in cockpit sole.
Engine Room Air	
External Intakes:	Manship® aluminum louvers painted.
Engine Room Air	
Internal Intakes:	Manship® Mist Eliminators in yard-built plenums with overboard drains.
Engine room finish:	White linear polyurethane.
Engine room sole:	FRP composite panels with non-skid surface.
Engine room spigot:	Fresh water.
Oil Pans:	FRP composite, under engines.
Generator Exhaust system:	Gas / water separator.
Exhaust system:	Volvo IPS exhaust system

MECHANICAL AND PLUMBING (CONTINUED)

Filter:	Fresh water.
Fire Extinguishers:	(5) at 2.5 lbs.
Fire Protection System:	Engine room, Sea-Fire automatic system with manual override
Fuel Filters:	Volvo fuel water separators. Racor fuel water separator for Generator.
Fuel Hose:	Fill, supply, return, vent; approved Type A1 and A2.
Fuel Tanks:	(2) of 5086 aluminum alloy, 450 USG total capacity.
Helm Instrumentation:	Volvo Single station; start/stop with electronic digital / analog displays.
Engines:	Twin Volvo IPS 600 with joystick control and helm instrumentation.
Fresh Water Pump:	Fresh water, with accumulator; 24V DC.
Water System:	Filtered fresh water at galley micro biological seagull IV x 1F purifier at galley
Fresh Water Regulator:	For dockside water connection.
External Sea Strainers:	For engine, generator, air conditioning pumps.
Engine Room Sound Insulation:	Mylar – faced foam with absorption layers.
Tank Gauges:	For fuel, water and waste tanks; 24V DC.
Black Water Tank:	FRP composite; 40 USG capacity.
Fresh Water Tanks:	(2) FRP composite with FDA-approved resin. 120 USG total capacity.
Toilets:	Jabsco Quiet Flush
Trim Tabs:	Lenco electric trim tabs.
Fuel Tank Vents:	For each tank; anti-spill vents.
Tank Vents:	For fresh water and black water tanks.
Fresh Water Washdown:	Spigot at foredeck.
Water Heater:	11USG 240VAC

ELECTRICAL

AC System:	115V AC, 230V AC.
DC System:	12V DC, 24V DC.
Engine Alternator:	(2) 24VDC, 60 Amp
Batteries:	(4) GPL-4D for engine and gen set. (2) GPL-8D for house. Stainless Steel hold down racks. Battery condition indicator with LED. Battery isolator
Battery Chargers:	230V AC / 24V DC, 60A.
Battery Switches:	With emergency paralleling capability.
Bonding System:	Bonding system with zinc anodes.
Carbon Monoxide Detectors:	In each stateroom, galley and saloon.
Engine Room Fans:	Manship , 24VDC
Engine Room Lights:	LED
Generator:	12KW Northern Lights; 115/230V AC, 60 Hz with sound enclosure.
Lighting:	LED and incandescent Down lights, accent lights, indirect lights, reading lights; 24V DC.
Outlets & Switches:	Vimar® décor colored covers, mounting frames, modular switches and UL boxes.
Panels:	AC systems; DC systems; battery management; gensets.
Shore Power Cable:	Glendinning Cablemaster®; 50 ft. white Hubbell® cable, 50 amp.
Shore Power:	230V AC.
Wire Fittings:	Marine grade terminals, connectors, fuses, fittings and conduit.
Wire:	Marine-grade, tinned copper.
Entertainment:	Proxicast LAN-Cell 3 cellular router & modem with an owner supplied service plan. The wireless network supports multiple Wi-Fi devices using cellular data networks.

ENSUITE HEAD

Exhaust Blower:	24V DC.
Head Accessories:	Towel racks, rings, hooks, soap trays, toothbrush holder, vanity mirror, toilet paper holder.
Head Stowage:	Lockers outboard of toilet; beneath vanity.
Outlet:	GFI protected
Mirrors:	(1) at vanity.
Portlights:	(1) fixed
Hatches:	(1) Manship® LDH-08-I 8-1/8" x 13-3/4". Hatch fitted with Manship screens/blinds.
Shower Fixtures:	Single-lever anti-scald type with rail-mounted hand-held shower head.
Shower Pan:	Moulded Oyster White FRP
Shower Sump:	24V DC.
Sink Fixtures:	Single Grohe in wall fixture
Sink:	White sink.
Toilet:	Jabsco Quiet Flush
Vanity top:	Solid Surface

GENERAL EXTERIOR OUTFIT

Air Horn:	Single trumpet, 24V DC.
Cleats:	Stainless steel
Deck Scuppers:	Stainless steel.
Salon Aft Doors:	(1) Manship® bi-parting, stainless steel sliding doors with fixed, full-height windows.
Flagstaffs:	Custom teak bow and stern ensign.
Grab Rails:	316 stainless steel 1.25" diameter.
Quarter Guard:	Heavy-duty vinyl extrusion; stainless steel half-oval striker.
Sheer Guard:	Heavy-duty vinyl extrusion; stainless steel half-oval striker.
Accommodations Hatches:	(1) Manship® LDH-50-I 19-1/2" x 19-1/2"; (3) Manship® LDH-08-I 8-1/8" x 13-3/4". Hatches fitted with Manship screens/blinds.
Courtesy Lights:	LED, 24V DC.
Navigation Lights:	On light mast, on deckhouse roof; LED, 24V DC.
Ports:	Tempered glass, fixed
Safety Rails:	1-1/4" 316 SS
Salon Hatches:	(2) Manship overhead opening hatches with screens and shades.
Deckhouse Side Windows:	Tinted tempered glass, fixed. Direct-glazed without frames.
Windshield Wipers:	Pantograph for all front windows. Variable speed, auto park, fresh water wash; 24 DC.
Deck:	Molded with nonskid
Cockpit Shade:	Powered Sureshade
Toe Rail:	Varnished teak

FOREDECK

Anchor Locker:	Self-draining, with access hatches.
Anchor Roller:	Custom stainless steel fabrication with single roller and chain stopper.
Anchor:	Stainless Steel CQR 35 lb., housed in roller.
Rope:	Combination rope/chain. 200 ft.
Windlass:	Maxwell RC10 vertical rope/chain windlass, 24VDC with Helm remote.

COCKPIT

Cushions:	Marine grade non-absorbing soft foam with Sunbrella covering.
Lighting:	LED, 24V DC.
Outlets:	115V AC with GFCI circuit protection.
Swim Platform Access:	Via starboard stairs with gate.
Table:	Varnished teak top with fixed stainless steel pedestal.
Storage:	Under aft seats
Transom Door:	Stainless steel gate to starboard

SWIM PLATFORM

Cleats:	Retractable type; stainless steel
Decking:	Laid teak, epoxy-bonded.
Platform:	Partially integral FRP moulding.
Swim Ladder:	Stainless steel Telescoping with boarding handle.
Transom Shower:	Shower with hot/cold mixing valve at transom door.

COMMISSIONING PACKAGE

Docking:	(2) Dock lines (5/8" x 35' bow and stern), 2 dock lines, (6) fenders (10" x 26") fender air pump, boat hook, garden hose (50' Neverkink)
Safety:	3 Fire Extinguishers (3B-1 or B-I & B-II), 3 Large Life Jackets, 1 Set of 4 Life Jackets, Throwable type IV, First Aid Kit, Flares, Horn
Signage:	Pollution Placard, MARPOL garbage placard, Copy of USCG navigation rules

Items and specifications are subject to change. Hunt Yachts reserves the right to modify, change or upgrade the specifications to meet quality requirements. Displacement is an estimate. Speeds are estimates and may vary depending on conditions. Capacities for tanks are estimates and useable